The VTS 258 cabinet is designed for daily use on laboratories. It offers an controlled and stabile environment for storing. It is user friendly and easy to clean. The VTS 258 features; Open door, high/low and power failure alarm, contact for remote alarm, as well as porthole for external monitoring systems.

#### **SPECIFICATIONS**

Temperature Range, °C	-60 to-86
Uniformity in performance, °C	4
Refrigerant	Nature R
Number of probes	1
Type of freezing	Static
Defrost	No
Internal air distribution	No
Number of compressors	2
Safety thermostat	No
Noise, dBA	64
Energy consumption, kWh/24h	12,8
Voltage, V	220-240
Frequency, Hz	50
Plug type	Schuko
Gross volume, litres (cu. ft.)	253 (8,93)
Net volume, litres (cu. ft.)	221 (7,80)
Inner Height, mm (inches)	1439 (56,65)
Inner Width, mm (inches)	440 (17,32)
Inner Depth, mm (inches)	375 (14,76)



#### **FEATURES**

Yes
Yes
Yes
Yes
Yes
4
Solid
No
2
Yes

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.



**VESTFR#ST**SOLUTIONS

A/S Vestfrost
Falkevej 12
DK-6705 Esbjerg Ø
www.vestfrostsolutions.com

# PRODUCT

## **VTS 258**

#### **EXCLUSIVE-86°C ULT FREEZER**

#### **STORAGE**

Shelfs	Yes
Shelfs material	Stainless steel
Number of shelfs incl bottom shelf (Standard)	5
Number of shelfs incl bottom shelf (max)	5
Max loading shelfs, kg (lbs)	16

#### **CONTROLLER**

Controller type	XW737K
USB Connection	Yes
Data connection	MODBUS
Controller languages	DA-GB-DE-PL- FR-IT-ES
Logs	35000
High/Low temperature alarm	Yes
Open door alarm	Yes
Power Failure alarm	Yes
Probe failure alarm	Yes
Temperature curve in controller	No

#### **OPTIONALS**

Chart recorder	No
----------------	----

#### **DIMENSIONS AND CONSTRUCTION**

Height, mm (inches)	2158 (85)
Width, mm (inches)	595 (23,4)
Depth, mm (inches)	650 (25,6)
Depth incl. doorhandle, mm (inches)	720 (28,3)
Gross weight, kg (lbs)	153,3 (337,96)
Net weight, kg (lbs)	139,2 (306,88
Material inner cabinet	Stainless steel
Material outer Cabinet	PVC coated gal- vanized steel
Insulation thickness	80 mm
Insulation type	Polyurethane with cyclopentane
Type of packaging	Cardboard with a wooden pallet

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.





**A/S Vestfrost** Falkevej 12

DK-6705 Esbjerg Ø www.vestfrostsolutions.com

# **DETAILS**

### **VTS 258**

#### **EXCLUSIVE-86°C ULT FREEZER**

- Designed and manufactured by A/S Vestfrost in Denmark
- · Unit optimized for optimal footprint
- DUAL compressor system with improved cooling capacity
- · Maintains -60°C with only 1 compressor running

## **ENVIRONMENT**

- · Eco-friendly, HCFC-free Nature R refrigerant
- · Efficient cyclopentane insulation
- · Low energy consumption

### **FEATURES**

- · Digital XW737K controller with display
- · 48 hours battery backup
- · Porthole for external monitoring systems
- · Top LED light for maximum visibility
- · Top-quality castors for explicit movability
- · Integrated lock to prevent unauthorized access
- · High/low temperature alarm

## QUALITY

- · User-friendly and maintenance-free
- · Dual compressor system
- · Galvanized, pre-painted steel cabinet







**TOP-QUALITY** castors eases repositioning of the VTS line units

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.



